Appl. No.

: 10/786,894

Filed

February 24, 2004

AMENDMENTS TO THE CLAIMS

IN THE CLAIMS:

Please cancel claim 6.

Please withdraw claims 10, 14, 19, and 23

Please amend claims 1, 24, and 25 as follows. Added matter is indicated by <u>underlining</u> and deleted matter is indicated by <u>strikethroughs</u> or double brackets ([[]]).

1. (Currently Amended) An intraocular lens, comprising: an optic made of a foldable material having:

an optical element with optical power;

a transition region disposed around the entire perimeter of the optical element, the transition region having a thickness of between at least about 0.07 mm and about 0.40 mm; and

a support disposed about at least a portion around the entire perimeter of the transition region, the thickness of the support being greater than the thickness of the transition region; at least two haptics integrally formed with the optic and coupled to the support.

- 2. (Original) The intraocular lens of claim 1, wherein the thickness of the support is between at least about 0.25 mm and about 0.60 mm.
- 3. (Original) The intraocular lens of claim 1, wherein the thickness of the transition region is at least about 0.12 mm.
- 4. (Original) The intraocular lens of claim 1, wherein the thickness of the haptics is less than or equal to the thickness of the support.
- 5. (Original) The intraocular lens of claim 1, wherein the material is selected from a group of deformable materials consisting of hydrogel, silicone, acrylic, and hybrid combinations of the same.
 - 6. (Canceled)
- 7. (Original) The intraocular lens of claim 1, wherein each haptic attaches at least at one location on the support.
- 8. (Original) The intraocular lens of claim 1, wherein each haptic attaches at least at two locations on the support.

Appl. No.

: 10/786,894

:

Filed

February 24, 2004

- 9. (Original) The intraocular lens of claim 1, wherein each haptic forms a substantially planar surface.
- 10. (Withdrawn) The intraocular lens of claim 1, wherein each haptic comprises a pair of pincer arms.
- 11. (Original) The intraocular lens of claim 1, wherein the intraocular lens is adapted for insertion into the capsular bag of an eye.
- 12. (Original) The intraocular lens of claim 1, wherein the intraocular lens is adapted for insertion into the anterior chamber of an eye.
- 13. (Original) The intraocular lens of claim 1, wherein the intraocular lens is adapted for insertion into the posterior chamber of an eye.
- 14. (Withdrawn) The intraocular lens of claim 1, wherein the optic further comprises a peripheral edge configured to inhibit cell growth on the intraocular lens.
- 15. (Original) An intraocular lens, comprising: an optic made of a foldable material having: an optical element with optical power; and
- a transition region around the entire perimeter of the optical element, the transition region having a thickness of between at least about 0.07 mm and about 0.40 mm; and
- at least two haptics integrally formed with the optic adapted to produce a positioning force when inserted into an eye;

means for isolating the positioning force from the optical element and the transition region.

- 16. (Original) The intraocular lens of claim 15, wherein the thickness of the transition region is at least about 0.12 mm.
- 17. (Original) The intraocular lens of claim 15, wherein the foldable material is selected from a group of deformable materials consisting of hydrogel, silicone, acrylic, and hybrid combinations of the same.
- 18. (Original) The intraocular lens of claim 15, wherein each haptic forms a substantially planar surface.
- 19. (Withdrawn) The intraocular lens of claim 15, wherein each haptic comprises a pair of pincer arms.

Appl. No.

: 10/786,894

:

Filed

February 24, 2004

- 20. (Original) The intraocular lens of claim 15, wherein the intraocular lens is adapted for insertion into the capsular bag of an eye.
- 21. (Original) The intraocular lens of claim 15, wherein the intraocular lens is adapted for insertion into the anterior chamber of an eye.
- 22. (Original) The intraocular lens of claim 15, wherein the intraocular lens is adapted for insertion into the posterior chamber of an eye.
- 23. (Withdrawn) The intraocular lens of claim 15, wherein the optic further comprises a peripheral edge configured to inhibit cell growth on the intraocular lens.
 - 24. (Currently Amended) A method of manufacturing an intraocular lens, comprising: providing a foldable material;

forming the material to produce an optic having:

an optical element with optical power;

a transition region disposed around the entire perimeter of the optical element, the transition region having a thickness of between at least about 0.07 mm and about 0.40 mm; and

a support disposed about at least a portion around the entire perimeter of the transition region, the thickness of the support being greater than the thickness of the transition region;

further forming the material to produce at least two haptics, the thickness of the haptics being less than or equal to the thickness of the support.

25. (Currently Amended) A method of inserting an intraocular lens into an eye, comprising:

providing an intraocular lens having:

an optic made of a foldable material having:

an optical element with optical power;

a transition region disposed around the entire perimeter of the optical element, the transition region having a thickness of between at least about 0.07 mm and about 0.40 mm; and

a support disposed about at least a portion-around the entire perimeter of the transition region, the thickness of the support being greater than the thickness of the transition region;

10/786,894

Appl. No. Filed February 24, 2004 :

> at least two haptics integrally formed with the optic, the thickness of the haptics being less than or equal to the thickness of the support

folding the intraocular lens;

creating an incision in an eye; and

inserting the intraocular lens through the incision and into a portion of the eye.